

OPEN FRAME MONITOR

Specification

Model Name	TSOPA-1700
Size	17 inch
Active Area(mm)	337.920(H) X 270.336(V)
Pixel Pitch(mm)	0.264(H) X 0.264(V)
Resolution	1280(H) X 1024(V)
Contrast Ratio	1000 : 1 (Typ)
Display Color	16.7M
Response time (R + F)	5 ms (typ)
Brightness(cd/m ²)	Typ. 250
Viewing Angle (L/R/U/D)	85/85/80/80
Operating Temperature	0 ~ 50 °C
Storage Temperuatre	0 ~ 50 °C
Signal Connector	(RGB, DVI)
Frame	Open Frame
Power Source	12V DC in, with External AC to DC Adapter
Power Consumption	15.6 W
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Product weight	3.6 Kg
Packing Information	490x360x470(H)mm (3pcs/ 15Kg)



< Option >

Signal Connector	HDMI, DP, S-Video, CVBS
Power source	DC 24V, AC 110~220V
Frame type	Chassis, Panel Mount, Rack Mount
Touch Screen	PCAP, IR, RES, SCAP, SAW, Glass
Dimming	Auto, Knob, Manual
temperature control	Heating , Cooling

* Dimming

- Industrial monitor : 5% Dimming (Zero Dimming : please ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

