CHASSIS FRAME MONITOR

□ Specification

| Model Name | TSCHA-1500 |
|-------------------------|-------------------------------------------|
| Size | 15 inch |
| Active Area(mm) | 304.128(H) X 228.096(V) |
| Pixel Pitch(mm) | 0.297(H) X 0.297(V) |
| Resolution | 1024(H) X 768(V) |
| Contrast Ratio | 700 : 1 (Typ) |
| Display Color | 262K, 16.2M |
| Response time (R + F) | 8 ms (typ) |
| Brightness(cd/m²) | Тур. 300 |
| Viewing Angle (L/R/U/D) | 80/80/80 |
| Operating Temperature | 0 - 50 'C |
| Storage Temperuatre | 0 - 50 'C |
| Signal Connector | (RGB, DVI) |
| Frame | Chassis Frame |
| Power Source | 12V DC in, with External AC to DC Adapter |
| Power Consumption | TBD |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Product weight | 3.8 Kg |
| Packing Information | 490x360x470(H)mm (3pcs/ 15Kg) |



| < Option > | | |
|---------------------|---------------------------------|--|
| Signal Connector | HDMI, DP, S-Video, CVBS | |
| Power source | DC 24V, AC 110~220V | |
| Frame type | Open, Panel Mount, Rack Mount | |
| Touch Screen | PCAP, IR, RES, SCAP, SAW, Glass | |
| Dimming | Auto, Knob, Manual | |
| temperature control | Heating , Cooling | |

* Dimming

- Industrial monitor : 5% Dimming (Zero Dimming : please ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

^{*} Specifications are subject to change without notice.

CHASSIS FRAME MONITOR

Mechanical Drawing

^{*} Specifications are subject to change without notice.