

# PANEL MOUNT FRAME MONITOR

## Specification

| Model Name                     | TSINE-1500                                |
|--------------------------------|---|
| Size                           | 15 inch                                   |
| Active Area(mm)                | 304.128(H) X 228.096(V)                   |
| Pixel Pitch(mm)                | 0.297(H) X 0.297(V)                       |
| Resolution                     | 1024(H) X 768(V)                          |
| Contrast Ratio                 | 700 : 1 (Typ)                             |
| Display Color                  | 262K, 16.2M                               |
| Response time (R + F)          | 8 ms (typ)                                |
| Brightness(cd/m <sup>2</sup> ) | Typ. 300                                  |
| Viewing Angle (L/R/U/D)        | 80/80/80/80                               |
| Operating Temperature          | 0 - 50 'C                                 |
| Storage Temperuatre            | 0 - 50 'C                                 |
| Signal Connector               | (RGB, DVI)                                |
| Frame                          | Panel Mount Frame                         |
| Power Source                   | 12V DC in, with External AC to DC Adapter |
| Power Consumption              | TBD                                       |
| Power Management               | VESA DPMS Compliant                       |
| Plug & Play                    | VESA DDC 1/2B                             |
| Product weight                 | 3.5 Kg                                    |
| Packing Information            | 500x400x130(H)mm (1pcs/ 5.5Kg)            |



### < Option >

|                     |                           |
|---------------------|---------------------------|
| Signal Connector    | HDMI, DP, S-Video, CVBS   |
| Power source        | DC 24V, AC 110~220V       |
| Frame type          | Open, Chassis, Rack Mount |
| Touch Screen        | Resistive, IR, Glass      |
| Dimming             | Auto, Knob, Manual        |
| temperature control | Heating , Cooling         |

#### \* Dimming

- Industrial monitor : 5% Dimming (Zero Dimming : please ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

\* Specifications are subject to change without notice.

# PANEL MOUNT FRAME MONITOR

## Mechanical Drawing



