

PANEL MOUNT FRAME MONITOR

Specification

Model Name	TSINE-W1010
Size	10.1 inch Wide
Active Area(mm)	216.96(H) X 135.6(V)
Pixel Pitch(mm)	0.1695(H) X 0.1695(V)
Resolution	1280(H) X 800(V)
Contrast Ratio	1300 : 1 (Typ)
Display Color	262K
Response time (R + F)	25ms (Typ)
Brightness(cd/m ²)	400 (Typ)
Viewing Angle (L/R/U/D)	80 / 80 / 80 / 80
Operating Temperature	0 - 50 'C
Storage Temperuatre	0 - 50 'C
Signal Connector	(RGB, DVI)
Frame	Panel Mount Frame
Power Source	12V DC in, with External AC to DC Adapter
Power Consumption	7.7 W
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Product weight	1.5 Kg
Packing Information	390x330x130(H)mm (1pcs/ 3.5Kg)

< Option >

Signal Connector	HDMI, DP, S-Video, CVBS
Power source	DC 24V, AC 110~220V
Frame type	Open, Chassis, Rack Mount
Touch Screen	Resistive, Glass
Dimming	Auto, Knob, Manual
temperature control	Heating , Cooling

* Dimming

- Industrial monitor : 5% Dimming (Zero Dimming : please ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

* Specifications are subject to change without notice.



