

HIGH BRIGHTNESS MONITOR

Specification

Model Name	TSVH-1701
Size	17 inch
Active Area(mm)	337.920(H) X 270.336(V)
Pixel Pitch(mm)	0.264(H) X 0.264(V)
Resolution	1280(H) X 1024(V)
Contrast Ratio	800 : 1 (Typ)
Display Color	16.7M
Response time (R + F)	30 ms (typ)
Brightness(cd/m²)	Min. 900
	Typ. 1000
Viewing Angle (L/R/U/D)	85/85/80/80
Operating Temperature	-30'C ~ 85'C
Storage Temperature	-30'C ~ 85'C
Signal Connector	(RGB, DVI)
Frame	Open Frame
Power Source	12V DC in, with External AC to DC Adapter
Power Consumption	25 W
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Product weight	3.6 Kg
Packing Information	490x360x470(H)mm (3pcs/ 18Kg)



< Option >


Signal Connector	HDMI, DP, S-Video, CVBS
Power source	DC 24V, AC 110~220V
Frame type	Chassis, Panel Mount, Rack Mount
Touch Screen	PCAP, IR, RES, SCAP, SAW
Dimming	Auto, Knob, Manual
Temperature control	Heating , Cooling


* Dimming

- Industrial monitor : 5% Dimming (Zero Dimming : please ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

HIGH BRIGHTNESS MONITOR

Mechanical Drawing





* Drawing is subject to change according to the specification