

HIGH BRIGHTNESS MONITOR

Mechanical Drawing

| | |
|-------------------------------------|---|
| Model Name | TSVH-W2380 |
| Size | 23.8 inch Wide |
| Active Area(mm) | 527.04(H) X 296.46(V) |
| Pixel Pitch(mm) | 0.2745(H) X 0.2745(V) |
| Resolution | 1920(H) X 1080(V) |
| Contrast Ratio | 3000 : 1 (Typ) |
| Display Color | 16.7 M |
| Response time (R + F) | 12 ms (typ) |
| Brightness(cd/m²) | Min. 650 |
| | Typ. 700 |
| Viewing Angle (L/R/U/D) | 89 / 89 / 89 / 89 |
| Operating Temperature | 0 ~ 50 'C |
| Storage Temperuatre | -20'C ~ 60'C |
| Signal Connector | (RGB, DVI) |
| Frame | Open Frame |
| Power Source | 12V DC in, with External AC to DC Adapter |
| Power Consumption | 27W |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Product weight | 5.9 Kg |
| Packing Information | 650x140x450(H)mm, 7.4kg |



< Option >

| | |
|---------------------|----------------------------------|
| Signal Connector | HDMI, DP, S-Video, CVBS |
| Power source | DC24V, AC 110~220V |
| Frame type | Chassis, Panel Mount, Rack Mount |
| Touch Screen | Glass |
| Dimming | Auto, Knob, Manual |
| Temperature control | Heating , Cooling |

* Dimming

- Industrial monitor : 5% Dimmin (Zero Dimmin : lease ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

* Drawing is subject to change according to the specification

