

HIGH BRIGHTNESS MONITOR

Model Name	TSVH-W2711
Size	27 inch Wide
Active Area(mm)	597.888(H) X 336.312(V)
Pixel Pitch(mm)	0.3114(H) X 0.3114(V)
Resolution	1920(H) X 1080(V)
Contrast Ratio	1000 : 1 (Typ)
Display Color	16.7 M
Response time (R + F)	14 ms
Brightness(cd/m²)	Min. 750
	Typ. 800
Viewing Angle (L/R/U/D)	89 / 89 / 89 / 89
Operating Temperature	0 - 50 'C
Storage Temperuatre	0 - 50 'C
Signal Connector	(RGB, DVI)
Frame	Open Frame
Power Source	12V DC in, with External AC to DC Adapter
Power Consumption	T.B.D
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Product weight	7 Kg,
Packing Information	720x500x160(H)mm, (1pc/ 9Kg)



< Option >

Signal Connector	HDMI, DP, S-Video, CVBS
Power source	DC24V, AC 110~220V
Frame type	Chassis, Panel Mount, Rack Mount
Touch Screen	PCAP, IR, Glass
Dimming	Auto, Knob, Manual
Temperature control	Heating , Cooling

* Dimming

- Industrial monitor : 5% Dimmin (Zero Dimmin : lease ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

*
Drawing
is
subject
to
change
accordi
ng to
the
specific
ation

Mechanical Drawing

