

HIGH BRIGHTNESS MONITOR

| Model Name | TSVH-W3211 |
|-------------------------------------|---------------------------------|
| Size | 32 inch Wide |
| Active Area(mm) | 698.4(H) X 392.85(V) |
| Pixel Pitch(mm) | 0.36375(H) X 0.36375(V) |
| Resolution | 1920(H) X 1080(V) |
| Contrast Ratio | 1300 : 1 (Typ) |
| Display Color | 16.7 M |
| Response time (R + F) | 25 ms |
| Brightness(cd/m²) | Min. 970 |
| | Typ. 1000 |
| Viewing Angle (L/R/U/D) | 89 / 89 / 89 / 89 |
| Operating Temperature | 0 ~ 50 'C |
| Storage Temperuatre | -20'C ~ 60'C |
| Signal Connector | (RGB, DVI) |
| Frame | Open Frame |
| Power Source | AC 110~ 220V |
| Power Consumption | 63W |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Product weight | 13 Kg |
| Packing Information | 850x170x560(H)mm (1pcs/ 17.5Kg) |



< Option >

| | |
|---------------------|----------------------------------|
| Signal Connector | HDMI, DP, S-Video, CVBS |
| Power source | DC 24V |
| Frame type | Chassis, Panel Mount, Rack Mount |
| Touch Screen | PCAP, IR, Glass |
| Dimming | Auto, Knob, Manual |
| Temperature control | Heating , Cooling |

* Dimming

- Industrial monitor : 5% Dimmin (Zero Dimmin : lease ask to Sales team)
- High-brightness monitor : 50% Dimming (5%, Zero Dimming : please ask to Sales team)

Mechanical Drawing

