

10.4 inch Flat Screen Frameless Touch Monitor

Projected Capacitive Touch screens/ Structure Water proof and Vandal proof



Open Frame Touch Monitor Parameters

General	
Model	TSCHA-104CJEL-PCT
Series	Flat Screen Frameless waterproof
Monitor Dimensions	Width: 269mm Height: 209mm Depth: 40mm
LCD Type	10.4" Active matrix TFT-LCD
Video Input	VGA and DVI
OSD controls	Allow on-screen adjustments of Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Power Supply	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max
Mount Interface	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical
LCD Specification	
Active Area(mm)	211.2x158.4 mm
Resolution	800x600 @60Hz
Dot Pitch(mm)	0.264x0.264
Nominal Input Voltage VDD	+3.3V(Typ)
Viewing angle (v/h)	70/70/60/70 (Typ.)(CR≥10)
Contrast	800:1
Luminance(cd/m2)	300
Response Time(Rising)	30 (Typ.)(Tr+Td) ms
Support Color	16.2M/262K colors
Backlight MTBF(hr)	10000(Min)
Touchscreen Specification	
Type	Projected Capacitive touch screen
Multi touch	5points touch
Touch Life Cycle	10 millions
Touch Response time	8ms
Touch System Interface	USB interface
Power consumption	+5V@80mA
External AC Power Adapter	
Output	DC 12V /4A
Input	100-240 VAC, 50-60 Hz
MTBF	50000 hr at 25°C
Environment	
Operating Temp.	0~50°C
Storage Temp.	-20~60°C
Operating RH:	20%~80%
Storage RH:	10%~90%

Components

USB Cable 180cm*1 Pcs, VGA Cable 180cm*1 Pcs,

Power Cord with Switching Adapter *1 Pcs, Bracket*2 Pcs

