18.5" Industrial Flat Screen Touch Monitor

Project Capacitive Touch screens with 10 points multi-touch

Surface waterproof meet IP65 standard ,Tempered glass and Vandal proof



Open Frame Touch Monitor Parameters

Display Specifica	ations			
T		alue	Comment	
LCD Size/Type	e/Type 18.5" a-S		i TFT-LCD	
Aspect Ratio		1	6:9	
Active Area		Horizontal	409.8mm	
		Vertical	230.4mm	
Pixel		Horizontal	0.300	
		Vertical	0.300	
Panel Resolution		1366(RGB)×768 (FHD)(75Hz)		Native
Display Color		16.7 Million		6-bits + Hi-FRC
Contrast Ratio		1000:1		Typical
Brightness		250 nits		Typical
Response Time		5	5ms Typical	
Viewing Angle		Horizontal	160	Typical
		Vertical	170	
Video Signal Input		VGA and DVI and HDMI		
Physical Specific	cations			
Dimensions		Width	454 mm	
		Height	277mm	
		Depth	40mm	
Electrical Specifi	cations			
Power Supply		DC 12V 4A		Power Adapter Included
		100-240 VAC, 50-60 Hz		Plug Input
Power Consumption		Operating	38 W	Typical
		Sleep	3 W	
		Off	1 W	
Touch Screen Sp	pecifications	5		
Touch Technology			Project Capacitive Touch Screen 10 Touch Point	
Touch Interface			USB (Type B)	
OS Supported	Plug and	Play	Windows All (HID) ,Linux (HID) (Android Option)	
Driver		Driver Offered		
Environmental S	pecification	S		
Condition			Specification	
Temperature		Operating	-10°C ~+ 50°C	
		Storage	-20°C ~ +70°C	
Humidity		Operating	20% ~ 80%	
		Storage	10% ~ 90%	
MTBF			30000 Hrs at 25°C	

Warranty and Components

1 Year Free Warranty for Monitor and all components.

USB Cable *1 Pcs VGA Cable *1 Pcs Power Cord with Switching Adapter *1 Pcs, Bracket*2 Pcs

HDMI Cable & DVI Cable Sold Separately

Mechanical Drawing

