

23.8" Industrial Open-Frame Touch Monitor

Project Capacitive Touch screens , 10 touch points ,3mm Tempered glass

Water-proof &vandal-proof

Open Frame Touch Monitor Parameters

Display Specifications			
Characteristic	Value		Comment
LCD Size/Type	23.8" a-Si TFT-LCD		
Aspect Ratio	16:9		
Active Area	Horizontal	527.04 mm	
	Vertical	296.46 mm	
Pixel	Horizontal	0.2745	
	Vertical	0.2745	
Panel Resolution	1920(RGB)×1080 (FHD)(60Hz)		Native
Display Color	16.7 Million		6-bits + Hi-FRC
Contrast Ratio	1000:1		Typical
Brightness	250 nits		Typical
Response Time	10 ms		Typical
Viewing Angle	Horizontal	178	Typical
	Vertical	178	
Video Signal Input	VGA and DVI and HDMI		
Physical Specifications			
Dimensions	Width	569.2 mm	
	Height	341.1 mm	
	Depth	43.4 mm	
Weight	Net Weight 7 kgs	Shipping Weight 9.5 kgs	
Box Dimensions	Length	660 mm	
	Width	440 mm	
	Height	180 mm	
Electrical Specifications			
Power Supply	DC 12V 4A		Power Adapter Included
	100-240 VAC, 50-60 Hz		Plug Input
Power Consumption	Operating	38 W	Typical
	Sleep	3 W	
	Off	1 W	
Touch Screen Specifications			
Touch Technology		Project Capacitive Touch Screen 10 Touch Point	
Touch Interface		USB (Type B)	
OS Supported	Plug and Play	Windows All (HID) ,Linux (HID) (Android Option)	
Driver		Driver Offered	
Environmental Specifications			
Condition		Specification	
Temperature	Operating	-10° C ~+ 50° C	
	Storage	-20° C ~ +70° C	
Humidity	Operating	20% ~ 80%	
	Storage	10% ~ 90%	
MTBF		30000 Hrs at 25° C	

Warranty and Components

1 Year Free Warranty for Monitor and all components.

USB Cable *1 Pcs, VGA Cable *1 Pcs,

Power Cord with Switching Adapter *1 Pcs,

Bracket*2 Pcs RS232 Cable & DVI Cable Sold Separately

