









## Features:

- 1. Fully enclosed design, the whole monitor is dustproof.
- 2. Seamless design flat bezel, front panel IP65 waterproof.
- 3. Aluminum alloy shell, good mechanical properties, excellent heat dissipation.
- 4. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.
- 5. High performance mainboard, 7x24 continuous operation.
- 6. VGA+HDMI+DVI interfaces, USB for touch.
- 7. 12-24V wide voltage support.
- 8. With waterproof rubber seal on the back side.
- 9. Support wall mounting, desk stand, embedded mounting.

## Model:TSINE-104-PCT **LCD** panel Panel size 10.4" Resolution 1024\*768 4:3 Aspect ratio Support Color 16.7M colors Brightness (cd/m²) 300+(high brightness optional) Contrast ratio 800:1 80°/85°/85°/80° (R/L/U/D) View angle Touch panel Project Capacitive Touch (10 points) Touchscreen Type 7Н Surface Hardness Luminousness 90% Touch Interface USB (RS232 optional) Touch response time 2ms Working Life >50 million times Touch options (5 wires restive touch optional) **Signal Ports** VGA 1x VGA DVI 1x DVI HDMI 1x HDMI Audio in/out Optional OSD OSD control Brightness, contrast ratio, auto adjustment, H/V position, language select, etc. Support languages English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc. Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect. Support OS

AC 100 - 240V, 50-60Hz  DC 12V  ≤10.5W  Aluminum Alloy		
DC 12V ≤10.5W		
≤10.5W		
Aluminum Allov		
Aluminum Allov		
· · · · · · · · · · · · · · · · · · ·		
Black, Silver		
75x75mm/100x100mm		
Front panel IP65 waterprod	of	
nt		
Operating: -10 to 60°C, sto	orage: -20 to 7	0°C
Operating: 10% to 80%, sto	orage: 5% to 9	0%
2.3kg		
3.8kg		
27.79*22.53*6.45cm		
43*38*18cm		
Power adapter, VGA cable, USB touch cable, embedded screws, user manual, warranty card		
Embedded mounting screv	vs	
Wall mounting brackets (o	ptional)	
Desk stand holder (optiona	al)	
tor		
277.9	30.5	263.7 263.7 2001 201 201 201
	Pront panel IP65 waterproduct Operating: -10 to 60°C, sto Operating: 10% to 80%, sto  2.3kg 3.8kg 27.79*22.53*6.45cm 43*38*18cm Power adapter, VGA cable, Embedded mounting screen Wall mounting brackets (o Desk stand holder (options)	Pront panel IP65 waterproof  Operating: -10 to 60°C, storage: -20 to 70 Operating: 10% to 80%, storage: 5% to 9  2.3kg 3.8kg 27.79*22.53*6.45cm 43*38*18cm Power adapter, VGA cable, USB touch call  Embedded mounting screws Wall mounting brackets (optional)  Desk stand holder (optional)  tor