

TSPC-2380AJ-PCT

Product Highlight

- 23.8 Inch LED Panel(1920 X 1080)
- 16 : 9(250cd/m2)
- Intel® Celeron J1900/2.0GHz Quad core processor
- Memory 4GB (option 8GB Upgrade)
- 128GB SSD (256GB, 512GB Upgrade)
- installation bracket Provide

specification

| | | |
|-----------------|----------------------|--|
| DISPLAY | LCD Size(Resolution) | 23.8"(1920 x 1080) |
| | Display Area (mm) | 527.04 (H) x 296.46 (V) |
| | Viewing Angle | 89/89/89/89 (Typ) (Left / Right / Up / Down) |
| | Brightness(cd/m2) | 250 (typ.) |
| | Contrast | 3000 : 1 (typ.) |
| | Aspect Ratio | 16 : 9 |
| | Touch Screen | Resistive (PCAP Option) |
| Hardware | CPU | Intel® Celeron J1900/2.0GHz Quad core processor |
| | Chipset | Adopt Intel® Bay trail SOC chipset |
| | BIOS | 64Mb Flash ROM |
| | Onboard Graphics | Intel® HD Graphics |
| | | 1 x VGA port, the highest resolution as 1920X1200@60HZ |
| | | 1 x HDMI port, the highest resolution as 2560 x 1600@60HZ |
| | Memory | 1 x SODIMM slot, support 1600/1333MHz DDR3L/1.35V memory |
| | | Max.Support up to 8GB Memory |
| | Hard Disk | Standard Mata SSD |
| | | SSD (MSATA) |
| | Onboard LAN | 8111F Gigabit Ethernet |
| | Audio | Integrated ALC662 6-Channel audio/Amplifier supports 2Ω5W speakers |
| | Rear I/O | 1 x HDMI 1.4ver |
| | | 1 x VGA |
| | | 1 x RJ-45 Gigabit Ethernet ports |
| | | 2 x USB 3.0 |
| | | 2 x USB 2.0 |
| | | 2 x RS232 serial ports(option) |
| | | 1 x WIFI ((option) |
| | | 1 x MIC |
| | 1 x Audio-out | |
| | 1 x 12V DC Jack | |

| | |
|-------------------|---|
| | Power on/off button |
| | HDD LED, Power LED |
| Power Consumption | TDP |
| Support OS | Windows 7 / Windows 8 / Windows 10 / Linux. |
| Environment | Operating Temperature: 0°C ~ 50°C |
| | Storage Temperature: -20°C ~ 70°C |
| Dimension | TBD |
| Weight | TBD |

Dimension



