







Features:

- 1. Robust and durable, all-metal enclosure, sealing design, full IP67 waterproof.
- 2. 23.8" Industrial LCD panel, 1000 nits. sunlight readable. Anti glare.
- 3. With dimmer on the bezel, Can adjust the brightness to 0-100%.
- 4. Adopt EETI waterproof touch solution. touch can work well with drop water on the screen.
- 5. Optical bonding technology.
- 6. Wide Temperature Range: operating: -20 to 70°C, storage: -30 to 80°C.
- 6. High performance mainboard, 7x24 continuous operation.

Model: TSIP-238-PCT	
LCD panel	
Panel size	23.8"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m²)	1000 nits, sunlight readable
Surface treatment	Anti glare
Contrast ratio	1000:1
View angle	89°/89°/89° (R/L/U/D)
Touch panel	
Touchscreen Type	Project Capacitive Touch (10 points)
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch optional)
Singal Ports	
VGA	1xVGA
HDMI	1xHDMI
DVI	optional
Audio in/out	optional
DP	optional

OSD		
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select etc.	
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese etc.	
11 3 3	·	
Support OS	Windows XP, Windwows /7/8/10, Linux, Mac OS X, Android, ect.	
Power Supply		
External Power Supply	AC 100-240V	
Working voltage	DC 12V	
Power consumption	≤40W	
Enclosure		
Material	aluminium alloy front bezel + High strength cold rolled steel back case	
Color	Black, white, Silver, color can be customized	
VESA mounting	75x75mm/100x100 mm	
IP-grade	Full IP67 waterproof	
Operating Environment		
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C	
Relative humidity	operating: 10% to 90%, storage: 5% to 90%	
Packing Details		
Net weight	7.5 kg	
Gross weight	8.5 kg	
Accessories	Power adapter, Waterproof Power cord, Waterproof VGA/HDMI/USB cable, Wall mount	
Other		
Mounting (options)	1) wall brackets for wall-mounting, VESA 100×100 mm	
	2) stable metal holder to support the monitor	
Warranty	1 year warranty	