



Features:

1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt multi-points PCAP touch panel, EETI waterproof solution, Touch can work well with drop water on the screen.
4. Brightness: 1000 nits, sunlight readable, Anti glare.
5. Optical bonding solution.
6. Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C.
7. Ultra-thin front bezel 3mm, ideal for embedded mounting in outdoor kiosk/ parking machine/ charging station and so on.
8. High performance motherboard, 7x24 continuous operation.

Model:TSPC-215

PC

CPU	Intel® Core i3-4005U
Memory	8G DDR3 (2G, 4G optional)
Hard Drive Capacity	128G SSD
Hard Drive Optional	SSD: 32G, 64GB, 256GB
	HDD: 500GB, 1TB
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1xRealtek RTL 8111E Gigabit Ethernet controller
Wireless Network	WIFI
I/O Interface	1xUSB 3.0, 3xUSB 2.0, 2xCOM RS232,1x RJ45
	1xVGA/HDMI/Audio OUT/POWER DC
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.

LCD panel

Panel size	21.5"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	1000 nits, sunlight readable
Response time	5ms
Contrast ratio	1000:1
View angle	80°/80°/80°/80° (R/L/U/D)

Touch panel	
Touchscreen Type	Project Capacitive Touch (10 points)
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50 million times
Touch options	(5 wire resistive touch optional)
Power Supply	
External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum Alloy bezel+high strong rolled steel back case
Color	Silver, Black, white, color can be customized
VESA mounting	75*75mm/100*100mm
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	Operating: -20 to 70°C, Storage: -30 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	6.7kg
Gross weight	8.1kg
Product Dimension	53.76×32.99×4.3 cm
Packing size	69×55×20 cm
Accessories	Power adapter, power cord, embedded screws
Other	
Mounting (options)	Embedded mounting screws
	Wall mounting brackets (optional)
	Desk stand holder (optional)
Warranty	1 year warranty