## **Product Description**



TDS capacitive touch screen is for Industrial use, support 7 inch to 65inch, Touch sensor's professional and experienced electrical circuit design works with ILITEK solution, makes the capacitive touch panel have high-quality grade and anti-interference ability. According to various Industrial tablets, All-in-one Computers, and control devices working environments, ILITEK serial can provide IK10, water-proof, dust-proof, anti- seismic, scratch resistant, glove touch, Thicker or Air-Gapped Touch Glass, IK10 etc different levels, and with stable running.



## 10.1 inch Capacitive(PCAP) Touch Panel | TDS101005H-AAA

| Projected Capacitive Touch Panel Specifications |  |
|---|--|
| Part No.  | TDS101005H-AAA                               |
| Technology                                      | Projected Capacitive Touch Technology (PCAP) |
| Screen Size                                     | 10.1"  |
| Glass Cover Dimension (Mm)                      | 255.4*167.4                                  |
| Glass Cover View Area (Mm)                      | 217.96*136.6                                 |
| Glass Cover Thickness (Mm)                      | 2  |
| Glass Cover R Angle (Mm)                        | 6.9  |
| Glass Cover Bezel Color                         | Black Color                                  |
| Touch Sensor Dimension (Mm)                     | 227.96*148.6                                 |
| Touch Sensor Active Area (Mm)                   | 219.56*138.2                                 |
| Light Transmittance                             | ≥85% ± 3%                                    |
| FPC Cable Location                              | DOWN   |
| Controller IC                                   | 0  |
| Controller IC Brand                             | ILITEK                                       |
| Controller Type                                 | COB+PCBA                                     |
| Controller Interface                            | USB 2.0                                      |
| Controller Operating Voltage                    | DC 4.5V ~ DC 5.5V                            |
| PCBA Model                                      | 0  |
| Number Of Touches                               | 10 Touch Points /1 Touch Point               |
| Durability                                      | Over 50 Million Touches In One Location      |
| Input Methods                                   | Fingers                                      |
|   | Rubber Gloves                                |
|   | Passive Stylus                               |
| Surface Treatment                               | Anti-Glare Option                            |

|                    | Anti-Fingerprint Option                 |
|--------------------|---|
|                    | Anti-Bacterial Option                   |
|                    | Privacy Filters Option                  |
|                    | Colored Borders Option                  |
|                    | Printed Icons Option                    |
| Operating System   | Windows XP                              |
|                    | Windows 7                               |
|                    | Windows 8                               |
|                    | Windows 10                              |
|                    | Android                                 |
|                    | Linux                                   |
| Temperature        | Operating : -10°C To -60°C              |
|                    | Storage : -20°C To -70°C                |
| Humidity           | Operating:20% ~85% (Non Condensing)     |
|                    | Storage: 0%~95% (Non Condensing)        |
| Durability         | Over 50 Million Touches In One Location |
| Installation Style | True Flat Integration                   |
|                    | Embedded Integration                    |
| Warranty           | 1 Year Free Warranty                    |
|                    | Extending Warranty Available            |
|                    |   |

<sup>\*</sup> The specification is subject to change without prior notice.