Product Description

TOUCH & DISPLAYS



TDS capacitive touch screen is for Industrial use, Touch sensor's professional and experienced electrical circuit design works with EETI solution, makes the capacitive touch panel have highquality grade and anti-interference ability. According to various Industrial tablets, All-in-one Computers, and control devices working environments, EETI serial can provide IK10, water-proof, dust-proof, anti- seismic, scratch resistant, glove touch, Thicker or Air-Gapped Touch Glass, IK10 etc different levels, and with stable running.



18.5 inch Capacitive(PCAP) Touch Panel | TDS185009H-BBB

Part No.	TDS185009H-BBB
Technology	Projected Capacitive Touch Technology (PCAP)
Screen Size	18.5″
Glass Cover Dimension (mm)	456.75*277.25
Glass Cover View Area (mm)	408.69*228.99
Glass Cover Thickness (mm)	1.1
Glass Cover R Angle (mm)	3.38
Glass Cover Bezel Color	Black Color
Touch Sensor Dimension (mm)	430.8*249.4
Touch Sensor Active Area (mm)	412.09*231.69
Light Transmittance	≥85% ± 3%
FPC Cable Location	DOWN
Controller IC	EXC81W60
Controller IC Brand	EETI
Controller Type	COB+PCBA
Controller Interface	USB
Controller Operating Voltage	DC 4.5V ~ DC 5.5V
PCBA Model	EXC81W604254STAG
Number Of Touches	10 Touch Points /1 Touch Point
Durability	Over 50 Million Touches In One Location
Input Methods	Fingers
Surface Treatment	Rubber Gloves
	Passive Stylus
	Anti-Glare Option
	Anti-Fingerprint Option
	Anti-Bacterial Option

Operating System	Privacy Filters Option
	Colored Borders Option
	Printed Icons Option
	Anti-Reflection Option
	Mirror Glass Option
	Shielding Film Option
	Windows XP
	Windows 7
	Windows 8
	Windows 10
	Android
	Linux
Temperature	Operating : -20°C To -70°C
	Storage : -30°C To -80°C
Humidity	Operating:20% ~85% (Non Condensing)
	Storage: 0%~95% (Non Condensing)
Durability	Over 50 Million Touches In One Location
Installation Style	True Flat Integration
	Embedded Integration
Warranty	1 Year Free Warranty
	Extending Warranty Available
Cover Glass Option	0.7 – 6 mm
Controller Interface Option	I2C/ Serial
Functional Debug Option	Water-proof, Oil-proof, Thicker or Air-Gapped Glass, Active Pen, Glove touch

* The specification is subject to change without prior notice.